

HIGHEST HOLDING POWER IN THE INDUSTRY

CARTON SEALING TAPE

HP SERIES

Nobody notices carton seals unless something goes wrong. Carton sealing tape should be strong enough to hold and tough enough to endure shipping abuse, yet release smoothly from the roll and deliver consistent tension in demanding high speed applications. A tall order? Not for the HP Series, only from Shurtape.

No other tape holds like Shurtape HP Series. From manual applications using hand rolls to automated packaging lines where our machine-length rolls maximize throughput, saving time and labor – HP performs right down to the core.

Shipping conditions may change, but our packaging tape performs consistently. Constructed of biaxially-oriented polypropylene (BOPP) film with our proprietary hot melt adhesive formula, HP Series has unequalled holding power, uncompromising strength, and superior moisture resistance, roll after roll.



HIGHEST HOLDING POWER IN THE INDUSTRY

CARTON SEALING TAPE



Time to Upgrade Your Tape Heads?

Are your tape heads hard-to-load and wear out before they should? Try our tape head program. With a signed agreement to purchase any HP machine-length product we'll give you a durable, stainless steel SP tape head. Our SP tape head, with one-touch adjustment, is easy to load, easy to clean, and ready to work.

Contact your Shurtape sales representative for more information.

REGIONAL SALES OFFICES & DISTRIBUTION CENTERS

North Carolina	Arizona
Corporate Headquarters 1506 Highland Avenue NE PO Box 1530 Hickory, NC 28603 tel: (828) 322-2700 (888) 442-8273 fax: (828) 322-4029	First Commerce Center 725 N 73rd Avenue, Suite 112 Phoenix, AZ 85043 tel: (623) 463-5886 (800) 342-8273 fax: (623) 463-5809

INTERNATIONAL SALES OFFICES & DISTRIBUTION CENTERS

US Corporate Headquarters	Canada	Europe	United Arab Emirates
Shurtape Technologies, LLC 1506 Highland Ave NE PO Box 1530 Hickory, NC 28603 USA tel: (828) 322-2700 (888) 442-8273 fax: (828) 322-4029 www.shurtape.com	Shurtape Technologies Co. 615 Bowes Road Concord, ON Canada L4K 1J5 tel: (905) 669-4881 (800) 463-8273 fax: (905) 669-2330 email: cproffitt@shurtape.com	Kip GmbH Schlavenhorst 9 (Industriepark) D-46395 Bocholt, Germany tel: +49 2871-23466-27 fax: +49 2871-23466-32 contact: Monica Ptok email: ptok@kip-tape.com www.kip-tape.com	Shurtape Ved Ltd. PO Box 11871 Dubai, United Arab Emirates tel: +971 (4) 881-3199 fax: +971 (4) 881-3166 email: shurtape@emirates.net.ae
Mexico	Peru	China	China
Shurtape Mexico, S de RL de CV Fraccionamiento Industrial Penuelas Paseo de la Constitucion #11 CP 76148, Queretaro, QRO Mexico tel: +52 (44) 2220-6367 fax: +52 (44) 2220-6366 email: shurtmex@prodigy.net.mx	Shurtape Peru S.A. Av. Minería 141-155 Urb. Fundo Puente-Santa Anita 43 Lima, Peru tel: +51 (1) 362-8212 fax: +51 (1) 362-0476 email: ventas@shurtapeperu.com	Shurtape Technologies (Shanghai) Co. Ltd. Songjiang Export Processing Zone No. 175 Block A West Maojing Road Shanghai 201611 P.R. China tel: +86 (21) 6772-5828 fax: +86 (21) 6772-5686 contact: Alvin Yeap email: info@shurtape.com.cn	Shurtape Technologies (Changshu) Co. Ltd. Changshu Southeast Economic Development Zone No. 188 Jinhua Road Changshu 215500 Jiangsu P. R. China tel: +86 (512) 5235-9500 fax: +86 (512) 5235-9599 email: info@shurtape.com.cn

Shurtape®

www.shurtape.com 1.888.442.TAPE

ISO 9000 CERTIFIED QUALITY SYSTEM

©2009 Shurtape Technologies, LLC
 "Shurtape" is a registered trademark of Shurtape Technologies, LLC.
 Printed in USA on recycled paper.
 Form #SS-HPSeries-03/23/2009-P2M

Shurtape®

www.shurtape.com 1.888.442.TAPE

HP SERIES

A TAPE FOR EVERY CARTON SEALING NEED

HP 100



HP 100 is designed for lightweight cartons exposed to minimal stress in shipping and handling. It sticks instantly to the carton yet unwinds easily from machine and hand rolls. It is an economical solution that performs consistently—making it a great value.

Tensile Strength	21 lbs/in width
Adhesion to Stainless Steel	42 oz/in width
Thickness	1.6 mils
Holding Power to Fiberboard (min)	10,000
Service Temperature Range	20°- 150° F

HP 200



For superior performance in automated industrial carton sealing processes, this instant seal production tape is ideal for sealing medium weight cartons in most manufacturing and shipping environments. Now available in transparent colors for inventory identification.

Tensile Strength	27 lbs/in width
Adhesion to Stainless Steel	44 oz/in width
Thickness	1.9 mils
Holding Power to Fiberboard (min)	15,000
Service Temperature Range	20°- 150° F

HP 232



This purpose-built tape securely seals cartons in cold-temperature environments such as produce packaging, meat and poultry processing, dairy facilities and cold weather moving and storage. It instantly sticks and stays in sub-freezing temperatures.

Tensile Strength	27 lbs/in width
Adhesion to Stainless Steel	30 oz/in width
Thickness	1.9 mils
Holding Power to Fiberboard (min)	10,000
Service Temperature Range	-20°- 100° F

HP 240/250



HP 240 and HP 250 security carton sealing tapes are lock printed—providing a durable message that will not rub off or degrade the adhesive. Three standard messages are in-stock: STOP - If Seal Is Broken; SECURITY TAPE. Custom messages (your company's name or marketing message) are available on HP 250 with adequate lead times and a minimum order.

Tensile Strength	27 lbs/in width
Adhesion to Stainless Steel	44 oz/in width
Thickness	1.9 mils
Holding Power to Fiberboard (min)	15,000
Service Temperature Range	20°- 150° F

HP 300



This instant seal, performance grade tape performs consistently in a wide variety of applications and environments. It's best for sealing medium-weight cartons subjected to increased handling stress.

Tensile Strength	30 lbs/in width
Adhesion to Stainless Steel	47 oz/in width
Thickness	2.2 mils
Holding Power to Fiberboard (min)	20,000
Service Temperature Range	20°- 150° F

HP 400



Large and heavy content cartons in automated or manual applications are no match for this instant seal high-performance tape. This tape is designed for high-stress, extreme-handling conditions. When high-speed, critical-closure production lines need secure seals, rely on HP 400.

Tensile Strength	33 lbs/in width
Adhesion to Stainless Steel	49 oz/in width
Thickness	2.5 mils
Holding Power to Fiberboard (min)	25,000
Service Temperature Range	20°- 150° F

HP 500



Our premium carton sealing tape, HP 500, is designed for heavy-duty cartons. It performs consistently on demanding packaging lines and holds strong under rigorous shipping conditions. It seals instantly to corrugated cartons, paper, film and a variety of other substrates—even cartons with high recycled content.

Tensile Strength	36 lbs/in width
Adhesion to Stainless Steel	53 oz/in width
Thickness	3.0 mils
Holding Power to Fiberboard (min)	30,000
Service Temperature Range	20°- 150° F

HP 800



Our thickest, toughest carton sealing tape yet. It's purpose-built to seal the bottoms of heavy-duty double and triple-walled cartons. HP 800 is extremely strong with an abrasion-resistant polyester film. It will hold strong in the most extreme handling conditions and meets the ASTM D5486 Type II standard.

Tensile Strength	54 lbs/in width
Adhesion to Stainless Steel	90 oz/in width
Thickness	3.4 mils
Holding Power to Fiberboard (min)	35,000
Service Temperature Range	20°- 150° F