

UV-RESISTANT

# STUCCO MASKING FILM TAPE

PE 444

Industrial poly-film tape for demanding indoor/outdoor applications.

Shurtape's PE 444 poly-film tape is the solution for indoor and outdoor stucco and masking applications - no matter how demanding. Only Shurtape offer a film tape with ultra-violet (UV) inhibitors to protect your project from the sun's damaging rays. And thanks to its special synthetic high-tack adhesive, PE 444 provides a watertight seal even in the most severe environments and weather conditions.

Despite its high tack, PE 444 removes cleanly with no residue. The quick clean up will help you cut back on man-hours and costly cleaning materials.

PE 444 is perfect for masking windows and doors for stucco applications. Its easy unwind and conformability make it ideal for general purpose uses. And it's designed to work on non-painted surfaces such as wood, vinyl, metal tile and other synthetic surfaces



**Shurtape®**

[www.shurtape.com](http://www.shurtape.com) 1.888.442.TAPE

UV-RESISTANT

# STUCCO MASKING FILM TAPE



## PE 444



**UV resistant Polyethylene Film Tape** for masking doors and windows during stucco application and painting.

- UV resistant
- High tack
- Watertight seal in severe environments and weather conditions
- Residue free

<b>Tensile Strength</b>	18 lbs/in width
<b>Adhesion to Stainless Steel</b>	67 oz/in width
<b>Thickness</b>	7 mils
<b>Elongation</b>	100 %
<b>Service Temperature Range</b>	32° to 160° F



## PE 555



**Heavy Duty Polyethylene Film Tape** for surface protection, splicing and seaming on pipe fitting covers, and color coding.

- Abrasion resistant
- Waterproof
- Excellent tear characteristics
- Conformable
- High tack adhesion

<b>Tensile Strength</b>	30 lbs/in width
<b>Adhesion to Stainless Steel</b>	67 oz/in width
<b>Thickness</b>	9.0 mils
<b>Elongation</b>	100 %
<b>Service Temperature Range</b>	32° to 160° F



## PC 622



**Premium Grade Duct tape** for media-blast stucco applications, protecting metal and plastic window frames, silk-screening and plastering.

- Provides moisture-proof barrier
- Super-high tensile strength
- High tack adhesive
- Conformable

<b>Tensile Strength</b>	40 lbs/in width
<b>Adhesion to Stainless Steel</b>	55 oz/in width
<b>Thickness</b>	12.5 mils
<b>Elongation</b>	10 %
<b>Service Temperature Range</b>	50° to 200° F

## PC 667



**UV resistant Cloth Duct Tape** for masking doors and windows during stucco, plastering and concrete applications.

- UV resistant up to 14 days
- Waterproof backing
- High tack adhesive
- Clean removal
- Conformable

<b>Tensile Strength</b>	22 lbs/in width
<b>Adhesion to Stainless Steel</b>	50 oz/in width
<b>Thickness</b>	9.0 mils
<b>Elongation</b>	15 %
<b>Service Temperature Range</b>	Up to 200° F

ISO 9000 CERTIFIED QUALITY SYSTEM

© 2010 Shurtape Technologies, LLC

"Shurtape" is a registered trademark of Shurtape Technologies, LLC.

♻️ Printed in USA on recycled paper.

Form #SS-PE444-09/01/2010-P1M

# Shurtape®

www.shurtape.com 1.888.442.TAPE