

SURFACE PRINTABLE HOTMELT PACKAGING TAPE

PRINTABLE HP

Our premium HP Carton Sealing Tape is now directly printable.

Your product speaks for itself. Don't let an unreliable tape distort its message.

When a client receives a product from you, its packaging says a great deal about what's waiting inside. Why let a poorly constructed tape get in the way of making a great first impression? With our Surface Printable HP Series, you can rest assured that all text and graphics will come through loud and clear – from hot off the printer to final delivery. From its rapid dry time to its ability to run at full line speeds, the Printable HP Series is designed with efficiency in mind.

This series also offers the highest level of shear strength available, so you know that the contents will arrive safely and securely. With the clearest prints and the strongest holds, place the strength of your brand and the quality of your product in our hands. **Insist that your printer converter uses only Surface Printable HP.**

Relax and unwind a roll from the Printable HP Series.



Shurtape®

www.shurtape.com 1.888.442.TAPE

PRINTABLE HOTMELT

SURFACE PRINTABLE HOTMELT PACKAGING TAPE



HP 260



For use on Siat L33, L36, L233 (or equivalent) printing presses

- Directly printable with all leading brands of solvent inks

- Exclusive release coat technology
- Superior ink anchorage without pickoff
- Quiet off the roll

Tensile Strength	27 lbs/in width
Adhesion to Stainless Steel	44 oz/in width
Thickness	1.9 mils
Elongation	130 %
Service Temperature Range	20° to 150° F



HP 460



For use on Siat L33, L36, L233 (or equivalent) printing presses

- Directly printable with all leading brands of solvent inks

- Exclusive release coat technology
- Superior ink anchorage without pickoff
- Quiet off the roll

Tensile Strength	21 lbs/in width
Adhesion to Stainless Steel	49 oz/in width
Thickness	2.5 mils
Elongation	145 %
Service Temperature Range	35° to 110° F



HP 560



For use on Siat L33, L36, L233 (or equivalent) printing presses

- Directly printable with all leading brands of solvent inks

- Exclusive release coat technology
- Superior ink anchorage without pickoff
- Quiet off the roll

Tensile Strength	36 lbs/in width
Adhesion to Stainless Steel	53 oz/in width
Thickness	3.0 mils
Elongation	150 %
Service Temperature Range	-35° to 110° F

REGIONAL SALES OFFICES & DISTRIBUTION CENTERS

North Carolina

Catawba Industrial Place
3389 Catawba Industrial Place
Catawba, NC 28609

tel: (828) 322-2700
(888) 442-8273
fax: (828) 322-4029

Arizona

First Commerce Center
725 N 73rd Avenue, Suite 112
Phoenix, AZ 85043

tel: (623) 463-5886
(800) 342-8273
fax: (623) 463-5809

INTERNATIONAL SALES OFFICES & DISTRIBUTION CENTERS

US Corporate Headquarters

Shurtape Technologies, LLC
1506 Highland Ave NE
PO Box 1530
Hickory, NC 28603 USA

tel: (828) 322-2700
(888) 442-8273
fax: (828) 322-4029
www.shurtape.com

Canada

Shurtape Technologies Co.
615 Bowes Road
Concord, ON
Canada L4K 1J5

tel: (905) 669-4881
(800) 463-8273
fax: (905) 669-2330
email: cproffitt@shurtape.com

ISO 9000 CERTIFIED QUALITY SYSTEM

© 2009 Shurtape Technologies, LLC

"Shurtape" is a registered trademark of Shurtape Technologies, LLC.

♻️ Printed in USA on recycled paper.

Form #SS-DISTRIBUTOR-01/11/2010-P1M

Shurtape®

www.shurtape.com 1.888.442.TAPE