

FOR ASBESTOS AND MOLD ABATEMENT

CONTRACTOR GRADE DUCT TAPE

PC 629

Our 11 mil solution for cold weather mold and asbestos abatement.

Our tape sticks. At temperatures as cold as 25° F. You can take it out of a cold truck, walk into a cold room and seal doors, walls, and windows with cold poly-sheeting.

And with our new high-tack adhesive with superior shear characteristics, you can expect PC 629 to hold up for the whole job. You get the quality Shurtape puts into every roll of tape we make. Easy to use because it's easy to tear. You won't waste tape because PC 629 doesn't curl or twist off the roll. Instant quick stick makes application fast and easy on poly-sheeting, metal, and unpainted wood. Ask for PC 629 today.

> **Works in cold weather**

Sticks to poly-sheeting at temperatures as cold as 25° F. Also works with metal and unpainted surfaces.

> **Holds up**

New high-tack adhesive with superior shear performance grabs quickly and seals dependably.

> **Reduces waste**

Does not curl, twist, or fold over to adhere to itself, becoming unusable and creating excess waste.



Shurtape | HOLD STRONG.

www.shurtape.com 1.888.442.TAPE

FOR ASBESTOS AND MOLD ABATEMENT

CONTRACTOR GRADE DUCT TAPE



PC 629

NEW



Contractor Grade Cloth Duct Tape for holding poly-sheeting in the asbestos and mold remediation industry.

- Excellent cold weather performance
- New high-tack adhesive
- Does not twist or curl off the roll

Tensile Strength	27 lbs/in width
Adhesion to Stainless Steel	65 oz/in width
Thickness	11.0 mils
Service Temperature Range	25° F to 200° F

PC 610

NEW



Industrial Grade Cloth Duct Tape for sealing walls, doors, and windows with poly-sheeting.

- Works in cold weather
- Instant quick stick
- Easy tear
- Won't twist or curl off the roll

Tensile Strength	22 lbs/in width
Adhesion to Stainless Steel	55 oz/in width
Thickness	10.0 mils
Service Temperature Range	25° F to 200° F

REGIONAL SALES OFFICES & DISTRIBUTION CENTERS

North Carolina

Corporate Headquarters
1506 Highland Avenue NE
PO Box 1530
Hickory, NC 28603
tel: (828) 322-2700
(888) 442-8273
fax: (828) 322-55839

Arizona

First Commerce Center
725 N 73rd Avenue, Suite 112
Phoenix, AZ 85043
tel: (623) 463-5886
(800) 342-8273
fax: (623) 463-5809
email: kking@shurtape.com

Missouri

Platte Valley Industrial Park
525 Northwest Parkway Drive
Riverside, MO 64150
tel: (816) 746-4488
(800) 790-4488
fax: (816) 746-4554

New Jersey

1320 Hamilton Street
Room 210
Somerset, NJ 08873
tel: (732) 246-0200
(800) 237-8273
fax: (732) 246-3272
email: ascimeca@shurtape.com

INTERNATIONAL SALES OFFICES & DISTRIBUTION CENTERS

US Corporate Headquarters

Shurtape Technologies, LLC
1506 Highland Ave NE
PO Box 1530
Hickory, NC 28603 USA
tel: (828) 322-2700
(888) 442-8273
fax: (828) 322-4029
www.shurtape.com

Canada

Shurtape Technologies Co.
615 Bowes Road
Concord, ON
Canada L4K 1J5
tel: (905) 669-4881
(800) 463-8273
fax: (905) 669-2330
email: cproffitt@shurtape.com

Europe

Kip GmbH
Schlavenhorst 9 (Industriepark)
D-46395 Bocholt, Germany
tel: +49 2871-23466-45
fax: +49 2871-23466-32
contact: Katja Leitner
email: info@kip-tape.com
www.kiptape.com

United Arab Emirates

Shurtape Ved Ltd.
PO Box 11871
Dubai, United Arab Emirates
tel: +971 (4) 881-3199
fax: +971 (4) 881-3166
email: shurtape@emirates.net.ae

Mexico

Shurtape Mexico, S de RL de CV
Fraccionamiento Industrial
Penuelas
Paseo de la Constitucion #11
CP 76148, Queretaro, QRO
Mexico
tel: +52 (44) 2220-6367
fax: +52 (44) 2220-6366
email: shurtmex@prodigy.net.mx

Peru

Shurtape Peru S.A.
Av. Minería 141-155
Urb. Fundo Puente-Santa Anita
43 Lima, Peru
tel: +51 (1) 362-8212
fax: +51 (1) 362-7472
email: ventas@shurtapeperu.com

China

Shurtape (Shanghai) Co. Ltd.
No. 175 Block A
West Maojing Road
Songjiang Export Processing Zone
Shanghai 201611
P.R. China
tel: +86 (21) 5774-9500
fax: +86 (21) 5774-9599
contact: Alvin Yeap
email: info@shurtape.com.cn

ISO 9000 CERTIFIED QUALITY SYSTEM

© 2006 Shurtape Technologies, LLC

"Shurtape" is a registered trademark of Shurtape Technologies, LLC.

♻️ Printed in USA on recycled paper.

Form #SS-PC629-04/06/2006-P1M

Shurtape®

www.shurtape.com 1.888.442.TAPE