

## TECHNICAL DATA

## TYPICAL APPLICATIONS

- > Non-critical construction and painting applications
- > General purpose packaging, bundling, holding, splicing and tabbing tape

## ADVANTAGES AND BENEFITS

- > Excellent adhesion and quick stick to vinyl, glass, plastic and rubber
- > Easy, clean surface release
- > Conforms to irregular surfaces and shapes without tearing or lifting

## CONSTRUCTION

Overall Grade/Function: Industrial Grade

Backing: Crepe paper

Adhesive: Solvent-less Rubber-based adhesive

## COLOR(S)



Natural (NAT)



## STANDARD WIDTH(S)

12 mm    18 mm    24 mm    36 mm    48 mm    72 mm

## STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.

## PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	20 lbs/in width	35.0 N/10 mm
Adhesion to Stainless Steel	33 oz/in width	3.61 N/10 mm
Thickness	5.2 mils	0.13 mm
Elongation	8 %	8 %
Service Temperature Range	50 F to 150 F	10 C to 66 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

## APPLICABLE STANDARDS

ASTM D6123/D6123M-07 Type I

## STORAGE &amp; USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.