

## TECHNICAL DATA

## TYPICAL APPLICATIONS

- > Commercial and residential painting and construction
- > Industrial masking, holding and packaging

## ADVANTAGES AND BENEFITS

- > Easy release off of the roll
- > Flexible
- > Good quick stick
- > Conforms well to irregularly-shaped surfaces
- > Paint and sundries industry standard

## CONSTRUCTION

Overall Grade/Function: Industrial/Professional Grade

Backing: Crepe paper

Adhesive: High Adhesion, Solvent less rubber-based adhesive



## COLOR(S)

Natural (NAT)

## STANDARD WIDTH(S)

12 mm    18 mm    24 mm    36 mm    48 mm    72 mm

## STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.

## PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	21 lbs/in width	36.8 N/10 mm
Adhesion to Stainless Steel	39 oz/in width	4.27 N/10 mm
Thickness	5.7 mils	0.14 mm
Elongation	8 %	8 %
Service Temperature Range	50 F to 150 F	10 C to 66 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

## APPLICABLE STANDARDS

ASTM D6123/D6123M-97 Type I; PPP-T-42C, Type I

## STORAGE &amp; USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.