

DT 200

Double-Coated
Non-Woven Tissue Coated Tape

Shurtape®

TECHNICAL DATA

TYPICAL APPLICATIONS

- > Designed for demanding corrugator splicing applications. Additionally, it is ideal for splicing of paper, plastics and other continuous web processes. Perfect for mounting and laminating irregular shaped metals, foams, foils, and nameplates.

ADVANTAGES AND BENEFITS

- > High adhesion and quick stick
- > Superior temperature resistance, able to withstand temps in corrugation process up to 400° F
- > Excellent conformability to most irregular surfaces
- > Outstanding mounting and laminating system for dissimilar metals, foams, foils and nameplates.
- > Excellent shear strength

CONSTRUCTION

Overall Grade/Function: Double-sided Splicing Tape

Backing: Non-woven tissue

Adhesive: Solvent acrylic, extremely aggressive

Liner: Bleached, poly-coated kraft



COLOR(S)

White (WHI)

STANDARD WIDTH(S)

48 mm

Contact your Shurtape sales representative for other available sizes.

STANDARD LENGTH(S)

50m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	5 lbs/in width	8.8 N/10 mm
Adhesion to Stainless Steel	60 oz/in width	6.57 N/10 mm
Thickness - with liner	9.0 mil	.23 mm
Thickness - without liner	4.5 mil	.11 mm
Elongation	3.5 %	3.5 %

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.