

TECHNICAL DATA

TYPICAL APPLICATIONS

- > Faux finishes, striping, most wall coverings and freshly cured paint

ADVANTAGES AND BENEFITS

- > Smooth flat-back paper that provides sharp clean paint lines with no adhesive transfer or paint bleed through
- > May be used on freshly painted surfaces and many wall coverings
- > Removes clean up to 30 days in direct sunlight


CONSTRUCTION

Overall Grade/Function: Multi-purpose

Backing: Smooth flat paper

Adhesive: Water-based acrylic

COLOR(S)

 Green (GRN)

STANDARD WIDTH(S)

18 mm 24 mm 36 mm 48 mm 72 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.



PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	21 lbs/in width	37 N/10 mm
Adhesion to Stainless Steel	15 oz/in width	1.6 N/10 mm
Thickness	4.3 mils	0.11 mm
Elongation	3 %	3 %
Adhesion to Backing	2 oz/in width	0.2 N/10 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE SPECIFICATIONS

ASTM D6123/D6123M-97

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.