

P- 691

Premium Grade  
Vinyl Coated Cloth Tape

# Shurtape®

## TECHNICAL DATA

### TYPICAL APPLICATIONS

- > Sealing containers and rooms
- > Abrasion protection
- > Holding and bundling

### ADVANTAGES AND BENEFITS

- > Waterproof backing
- > Abrasion resistant
- > Conformable
- > Performs well over a wide temperature range
- > Hand tearable

### CONSTRUCTION

Overall Grade/Function: Premium Grade

Backing: Vinyl coated cloth

Adhesive: Synthetic rubber

### COLOR(S)



Black (BLK)



Gray (GRY)



Olive Drab (OLV)



White (WHI)



### STANDARD WIDTH(S)

48 mm      72 mm

### STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.

### PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	69 lbs/in width	120.8 N/10 mm
Adhesion to Stainless Steel	60 oz/in width	6.57 N/10 mm
Thickness	14 mils	0.36 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

### APPLICABLE STANDARDS

CID A-A-1586A

### STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

"Shurtape" is a registered trademark of Shurtape Technologies, LLC

Form# TDS-P-691-12/6/2011