

PC 610

Industrial Grade

Polyethylene/Cloth Duct Tape

Shurtape®

TECHNICAL DATA

TYPICAL APPLICATIONS

- > Holding poly-sheeting in the asbestos/mold remediation industry

ADVANTAGES AND BENEFITS

- > High adhesion and tack
- > Does not twist or curl off of roll
- > Excellent cold weather performance


CONSTRUCTION

Overall Grade/Function: Industrial Grade

Backing: Polyethylene/Cloth laminate

Adhesive: Blended rubber

COLOR(S)

 Metallic Silver (SIL)

STANDARD WIDTH(S)

48mm 72mm

STANDARD LENGTH(S)

55m

*Contact your Shurtape sales representative for other available sizes.



PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	21 lbs./in. width	36.8 N/10mm
Adhesion to Stainless Steel	45 oz./in. width	4.93 N/10mm
Thickness	10.0 mils	.25 mm
Elongation	18 %	18 %
Service Temperature Range	25 F to 200 F	-4 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.