

TECHNICAL DATA

TYPICAL APPLICATIONS

- > HVAC, industrial, commercial, utilities, trucking and automotive
- > Holding, securing, seaming, repairing, bundling, splicing, packaging, masking and as a moisture barrier



ADVANTAGES AND BENEFITS

- > Waterproof backing
- > Excellent conformability and tack
- > Easy unwind and tear
- > Excellent holding power
- > Wide variety of colors

CONSTRUCTION

Overall Grade/Function: Industrial Grade
 Backing: Waterproof, polyethylene film with a polyester/cotton blend cloth carrier
 Adhesive: Natural rubber

COLOR(S)

 Silver (SIL)

STANDARD WIDTH(S)

24 mm 48 mm 72 mm

STANDARD LENGTH(S)

55 m
 Contact your Shurtape sales representative for other available sizes.



PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	27 lbs/in width	47.3 N/10 mm
Adhesion to Stainless Steel	63 oz/in width	6.90 N/10 mm
Thickness	10 mils	0.25 mm
Elongation	16 %	16 %
Service Temperature Range	50 F to 200 F	10 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE STANDARDS

Tested in accordance with UL 723; FSI 15/SDI 25; US Green Building Council – LEED® Point Contributor Product

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.