

TECHNICAL DATA

TYPICAL APPLICATIONS

- > Sealing, waterproofing, holding, camouflaging, sound deadening, covering reflective surfaces, and patching applications

ADVANTAGES AND BENEFITS


- > Official Army ACU digital camouflage pattern
- > Waterproof backing
- > Conformable



CONSTRUCTION

Overall Grade/Function: Specialty Grade  
 Backing: Waterproof, polyethylene film with a polyester/cotton blend cloth carrier  
 Adhesive: Natural rubber

COLOR(S)

 Army Digital Camouflage (CAM)

STANDARD WIDTH(S)

48 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	23 lbs/in width	40.3 N/10 mm
Adhesion to Stainless Steel	42 oz/in width	4.60 N/10 mm
Thickness	10 mils	.25 mm
Elongation	29 %	29 %
Service Temperature Range	50 F to 200 F	32 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.