

TECHNICAL DATA

TYPICAL APPLICATIONS

- > Rough Surfaces
- > Heavy Repairs
- > Bottom Board Tape in Manufacturing Housing



ADVANTAGES AND BENEFITS


- > Extra thick adhesive for quick stick on rough surfaces
- > Superior Strength High-count cloth
- > Waterproof backing provides durable protection

CONSTRUCTION

Overall Grade/Function: Specialty Grade
Backing: Polyethylene
Adhesive: Natural Rubber



COLOR(S)

 Metallic Silver (MSL)

STANDARD WIDTH(S)

48 mm

STANDARD LENGTH(S)

40 yd

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	46 lbs/in width	80.6 N/10 mm
Adhesion to Stainless Steel	102 oz/in width	11.16 N/10 mm
Thickness	17 mils	0.43 mm
Elongation	10 %	10 %
Service Temperature Range	50 F to 200 F	10 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.