

**TECHNICAL DATA**

**TYPICAL APPLICATIONS**

- > California Energy Commission (CEC) Approved-ASTM 2342-03 tested, specialty grade cloth duct tape
- > Designed specifically for HVAC Class 1 flex duct applications
- > Installing air ducts and air connectors and making connections and splices
- > Conforms to the 2005 and 2008 California Building Energy Efficiency Standard (Section 124(b) 1D, 124(b) 2D, 150(m) 3D and can be used to seal flex duct to fitting joints without being in combination with mastic.
- > Uses in which tensile strength and adhesion to stainless steel and polyethylene must meet or exceed the strict requirements of UL, flex duct manufacturers, and city and state codes



**ADVANTAGES AND BENEFITS**

- > California Energy Commission (CEC) Approved
- > UL 181B-FX Listed for Class 1 Duct
- > Green Point Contributor Product
- > Resistance to flame spread, smoke generation, mold growth, humidity and the effects of high temperatures
- > Tested in accordance with ASTM 2342-03, standard test method for longevity testing of duct sealant methods
- > Superior shear strength
- > Excellent tear characteristics


**CONSTRUCTION**

**Overall Grade/Function:** Premium Grade, CEC Approved  
ASTM 2342-03 tested, UL 181B-FX Listed

**Backing:** Waterproof, metalized polyethylene film with a polyester/cotton blend cloth carrier

**Adhesive:** Synthetic Rubber Blend

**COLOR(S)**

 Silver Metalized Printed (SMT)



**STANDARD WIDTH(S)**

48 mm 72 mm

**STANDARD LENGTH(S)**

55 m

Contact your Shurtape sales representative for other available sizes.

**PHYSICAL PROPERTIES**

	STANDARD	METRIC
Tensile Strength	27 lbs/in width	47.3 N/10 mm
Adhesion to Stainless Steel	70 oz/in width	7.66 N/10 mm
Thickness	13.5 mils	0.34 mm
Elongation	12 %	12 %
Service Temperature Range	50 F to 212 F	10 C to 100 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

**APPLICABLE STANDARDS**

ASTM 2342-03; FSI 5/SDI 10; Tested in accordance with UL 723; UL181B-FX Listed; UL Listed; US Green Building Council – LEED® Point contributor product

**STORAGE & USAGE CONDITIONS**

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

"Shurtape" is a registered trademark of Shurtape Technologies, LLC

Form# TDS-PC857- 7/18/2011