

TEMPERATURE-RESISTANT, CLEAN REMOVAL

HIGH PERFORMANCE MASKING TAPES

Some industrial applications, like painting and metal fabrication, require a masking tape that can withstand high temperatures. These applications also demand a tape that won't leave behind a residue upon removal. It's why we engineered our High Performance Masking Tapes to the highest of standards – to give you the heat resistance, clean removal and sharp paint lines you expect.

These premium masking tapes offer various levels of heat resistance, withstanding a range of temperatures from 200 F up to 350 F. When subjected to extreme temperatures, cured rubber adhesive systems allow for residue-free removal from most metals, rubber, plastics, gel-coat and other surfaces.

Shurtape® High Performance Masking Tapes conform well to irregular surfaces, are made with strong crepe paper backings that resist tears and slivers, and are designed to block solvents and moisture to minimize paint bleed-through and rework.








HIGH PERFORMANCE

SHURTAPE.COM 1.888.442.TAPE

Shurtape®
TRUE TO YOUR WORK™

TEMPERATURE-RESISTANT, CLEAN REMOVAL

HIGH PERFORMANCE MASKING TAPES

		Tensile	Adhesion to Stainless Steel	Thickness	Elongation	Service Temperature Range
CP 400	 <p>High performance grade masking tape designed for moderate temperature applications in the transportation industry</p> <ul style="list-style-type: none"> • Easy handling • Sharp paint lines • Clean removal • Economical 	24 lbs/in width	34 oz/in width	5.7 mils	10%	32 - 200 F
CP 450	 <p>High performance grade masking tape designed for demanding moderate temperature applications in the transportation industry</p> <ul style="list-style-type: none"> • Resists paint bleed-through • Solvent and moisture resistant • Clean removal • Ideal for wet sanding 	31 lbs/in width	37 oz/in width	6.9 mils	10%	32 - 225 F
CP 500	 <p>High performance grade masking tape designed for high temperature painting on cars, buses and wet sanding applications</p> <ul style="list-style-type: none"> • Easy unwind • Sharp paint lines • Resists solvents • Excellent quick stick 	26 lbs/in width	43 oz/in width	5.8 mils	9%	45 - 300 F
CP 650	 <p>High performance grade masking tape designed for high temperature painting in the transportation industry</p> <ul style="list-style-type: none"> • Solvent and moisture resistant • Withstands multiple bake cycles • Clean removal 	28 lbs/in width	37 oz/in width	6.6 mils	11%	45 - 325 F
CF 740	 <p>High performance grade masking tape designed for very high temperature applications in the transportation, marine and metal fabrication industries</p> <ul style="list-style-type: none"> • Easy unwind • Resists paint bleed-through • No residue 	25 lbs/in width	39 oz/in width	6.3 mils	11%	45 - 350 F



SHURTAPE.COM 1.888.442.TAPE



Shurtape®
TRUE TO YOUR WORK™

ISO 9001 CERTIFIED QUALITY SYSTEM © 2017 Shurtape Technologies, LLC
Printed in USA on recycled paper. Form #SS-HP Masking-01/24/2017-E