

AF 100 ALUMINUM FOIL TAPE WITH EASYPEEL® LINER

Dealing with a hard-to-start liner on a roll of tape while on the job can be frustrating and wastes time. That's why Shurtape® added EasyPEEL®, an innovative split liner technology, to its trusted AF 100 UL 181A-P/B-FX Listed and printed aluminum foil tape. Designed for a smooth start and fast finish, AF 100 with EasyPEEL is the same UL compliant tape that delivers airtight performance, now enhanced with a crack and peel liner that's easy to start so you can get the job done quickly and hassle-free.



SUPERIOR RESULTS: Delivers full system closure – and code compliance – when sealing joints, connections and seams on rigid fiberglass ductboard and flexible air duct in application temperatures ranging from -20 F to 260 F and in humid conditions.

UNRIVALED CONVENIENCE: Crack and peel liner is quick and easy to start, even while wearing gloves, to save you time, money and frustration on the job.



AF 100

AF 100 ALUMINUM FOIL TAPE WITH EASYPEEL® LINER

AF 100



UL 181A-P/B-FX Listed and printed aluminum foil tape for use on rigid fiberglass ductboard and flexible air duct, as well as for use when repairing metal and sheet metal

- Available with traditional liner or EasyPEEL® split liner technology
- Flexible and easy to use to create airtight bonds
- Superior stability during extreme fluctuations in temperature
- High-tack acrylic cold temperature adhesive

Tensile	Adhesion to Stainless Steel	Thickness (without liner)	Elongation	Service Temperature Range
25 lbs/in width	70 oz/in width	4.2 mils	2%	-20 F - 260 F



SHURTAPE.COM 1.888.442.TAPE



Shurtape®
TRUE TO YOUR WORK™