

SURFACE PRINTABLE, HOT MELT

PACKAGING TAPES

When a client receives your product, you rely on the package to communicate for you. And, you expect your message to read loud and clear, especially as your packaging says a great deal about you and the product that's contained inside. It's why Surface Printable HP Series packaging tapes from Shurtape® are crafted to help you make a great first impression.

Combining the same premium performance qualities you expect from our HP Series packaging tapes with a directly printable surface that offers superior ink anchorage without pickoff, Printable HP Series communicates your text and graphics cleanly and clearly.

For use on L33, L36 and L233 (or equivalent) flexographic printing presses, Printable HP Series is designed with efficiency in mind. It offers faster drying times, the ability to run Siat machines at full line speeds (450 ft/min), and an exclusive release coat technology that allows for consistent – and quieter – unwind. And, with the highest shear strength adhesive available, you know your contents will arrive safely and securely.

SURFACE PRINTABLE, HOT MELT

PACKAGING TAPES

HP 260



Directly printable, production grade hot melt packaging tape used in manual and automated industrial carton sealing of medium-weight cartons in everyday manufacturing and shipping environments.

HP 460



Directly printable, high performance grade hot melt packaging tape recommended for higher speed, critical closure carton sealing of large, bulky or heavy content cartons in manual or automated industrial sealing environments.

HP 560



Directly printable, heavy duty grade hot melt packaging tape for manual or automated industrial sealing of heavy, bulky cartons, including overstuffed or under-filled cartons, in high stress and extreme handling conditions. Designed to be tough.

GS 496



Directly printable, general purpose, fiberglass-reinforced hot melt strapping tape for strapping, packaging, bundling and palletizing applications.

TECHNICAL SPECIFICATIONS

		Tensile	Adhesion to Stainless Steel	Thickness	Elongation	Service Temperature Range	Application Temperature Range
HP 260	Surface printable, production grade hot melt packaging tape for medium-weight carton sealing.	27 lbs/in width	44 oz/in width	1.9 mils	150%	-20 - 150 F	35 - 110 F
HP 460	Surface printable, high performance grade hot melt packaging tape for securing large, bulky or heavy content cartons.	33 lbs/in width	54 oz/in width	2.5 mils	150%	-20 - 150 F	35 - 110 F
HP 560	Surface printable, heavy duty grade hot melt packaging tape for sealing in high-stress and extreme handling conditions.	42 lbs/in width	58 oz/in width	3 mils	150%	-20 - 150 F	35 - 110 F
GS 496	Directly printable, production grade hot melt strapping tape with fiberglass-reinforced backing.	100 lbs/in width	70 oz/in width	4.5 mils	3.7%	-10 - 150 F	-



SHURTAPE.COM
1.888.442.TAPE



Shurtape®
TRUE TO YOUR WORK™

ISO 9001 CERTIFIED QUALITY SYSTEM © 2017 Shurtape Technologies, LLC
© Printed in USA on recycled paper. Form #SS-HP Printer Converter-12/19/2019