

PC 9S



by **Shurtape®**

GENERAL PURPOSE, CONTRACTOR GRADE, CO-EXTRUDED DUCT TAPE

TYPICAL APPLICATIONS

- For heavy duty sealing, seaming, repairing, bundling, holding and waterproofing applications that require aggressive stick and superior hold
- Also used in the restoration industry for tasks such as hanging poly-sheeting
- For temporary or permanent use

PRODUCT FEATURES

- Excellent cold temperature performance
- Aggressive, high-tack adhesion
- 30-day indoor clean removal on most surfaces
- All-weather durability
- Consistent, low-force unwind off the roll
- Hand-tearable in machine and cross directions
- Made using Polybonded CO-EX Technology® to increase the tape's strength and ability to withstand repeated stress

CONSTRUCTION

Overall Grade/Function: General Purpose

Backing: Waterproof polyethylene film with a cloth carrier

Adhesive: Natural rubber

STANDARD WIDTH(S)

48 mm 72 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



SILVER
(SIL)

PHYSICAL PROPERTIES	STANDARD	METRIC
Tensile Strength	26 lbs/in width	45.5 N/10 mm
Adhesion to Stainless Steel	80 oz/in width	8.76 N/10 mm
Thickness (Nominal)	9 mils	0.23 mm
Elongation	20%	20%
Service Temperature Range	35 F to 200 F	2 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

