

# PC 590

**Shurtape®**  
TRUE TO YOUR WORK™

## UTILITY GRADE, CO-EXTRUDED CLOTH DUCT TAPE

### TYPICAL APPLICATIONS

- For non-critical, general purpose use in packaging, bundling, sealing, seaming, repairing, holding and waterproofing
- Also used in the remediation and restoration industries

### PRODUCT FEATURES

- Good adhesion and conformability
- Will not twist or curl during application
- Made using Polybonded CO-EX Technology®

### CONSTRUCTION

Overall Grade/Function: Utility

Backing: Waterproof polyethylene film with a cloth carrier

Adhesive: Natural rubber

### STANDARD WIDTH(S)

48 mm

### STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes

### STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

### COLOR(S)



**SILVER**  
(SIL)



**BLACK**  
(BLK)

### PHYSICAL PROPERTIES STANDARD METRIC

Tensile Strength	20 lbs/in width	35.0 N/10 mm
Adhesion to Stainless Steel	54 oz/in width	5.91 N/10 mm
Thickness	7 mils	0.18 mm
Elongation	20%	20%
Service Temperature Range	32 F to 200 F	0 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

