

YOU DEMAND FULL SYSTEM CLOSURE.

And rely on tape to get the job done quickly and efficiently. That’s why we offer a full portfolio of foil, film and composite HVAC tapes that deliver the product features and full system closure you demand. With options to meet the code, perform in the cold, and seal a broad range of HVAC materials, Shurtape has you covered with the tapes you need to ensure airtight performance you can be proud of.

In addition to providing the tools you need to get the job done, we have also developed resources dedicated to keeping you up to date on industry trends and best practices – to help you exceed expectations on the job.

Our educational website, TapeUniversity.com, is your leading online resource for all things tape. We’re committed to building the best learning experience by providing the tape industry’s most comprehensive place to learn about the past, present and future trends on choosing and using tape. From blog posts and articles to video demonstrations, Tape University serves to answer the industry’s most commonly asked questions about tape – and invites you to ask your own.



GOT A QUESTION ABOUT TAPE?

TAPEUNIVERSITY

Join the conversation at tapeuniversity.com



SHURTAPE.COM 1.888.442.TAPE



SHURTAPE.COM 1.888.442.TAPE



TAPE SOLUTIONS FOR HVAC



PC 622



Premium grade cloth duct tape used for sealing and seaming duct systems in the HVAC industry. PC 622 combines high tensile strength, excellent holding power and conformability to deliver a tape solution that can withstand the rigors of the job.

SF 682/683



ShurFLEX® HVAC professional grade metalized cloth duct tape designed for airtight and moisture-free seaming, connecting, splicing, patching and sealing of sheet metal and flex duct, rigid ductboards, air vents, insulation, fibrous filter banks and pollution collection systems. For superior performance, SF 682 and 683 are easy to use, are hand tearable and designed in color and appearance to match sheet metal, flex duct and ductboard.

MJ 100



Open weave fiberglass mesh tape used for reinforcing joints, seams and connections when paint-on mastic is used in HVAC applications, and can also be applied to drywall seams before the application of joint compound. MJ 100 drywall tape is self-adhering and offers superior strength compared to paper.

PC 857



UL 181B-FX Listed and printed cloth duct tape used to seal, seam and join Class 1 Flex Duct, even when surfaces are rougher or not fully clean. PC 857 offers high adhesion, superior shear strength and excellent tearability, and is recommended for applications that must meet or exceed the strict requirements of UL, flex duct manufacturers and city and state codes.

SF 685



ShurMASTIC® roll mastic tape for indoor or outdoor use to seal sheet metal and PVC-coated duct in temperatures up to 200 F. SF 685 is a lined, paintable foil tape that’s tested in accordance with UL 723 and delivers permanent, airtight and water-resistant seals.

VP 410



UV-resistant SPVC line set tape used in the HVAC industry to wrap line sets, seam Rubatex and Armaflex, and insulate air ducts and underground pipes. VP 410 is engineered with a non-corrosive adhesive and flexible backing; can be used in extensive temperature, moisture and humid conditions; and meets OSHA color-coding requirements.

PC 858CA



California Energy Commission (CEC) approved cloth duct tape used to seal, seam and join Class 1 Flex Duct, and can also be used to seal flex duct to fitting joints without mastic. UL 181B-FX Listed PC 858CA offers superior shear strength and excellent tearability, and is recommended for applications that must meet or exceed the strict requirements of UL, flex duct manufacturers and city and state codes.

SF 686



ShurMASTIC® butyl foil tape used for airtight and moisture-free sealing of Class 1 Flex Duct, sheet metal, PVC-coated duct and duct wrap vapor barriers, and is also approved for subgrade application on PVC-coated duct. A paintable, UL 181B-FX Listed mastic on a roll for indoor or outdoor use, SF 686 is designed with a butyl rubber adhesive system that can withstand wide temperature variances once applied.

SHURTAPE.COM 1.888.442.TAPE



“Shurtape,” “ShurFLEX,” and “ShurMASTIC,” are registered trademarks of Shurtape Technologies, LLC.



ISO 9001 CERTIFIED QUALITY SYSTEM © 2020 Shurtape Technologies, LLC
® Printed in USA on recycled paper. Form #SS-HVAC-Tapes-01/10/2020

TAPE SOLUTIONS FOR HVAC

AF 100

UL 181 A-P/B-FX Listed aluminum foil HVAC tape for joining and sealing joints, connections and seams on rigid fiberglass ductboard and flexible air duct. A tape that “does it all,” AF 100 is engineered to form airtight bonds on joints and seams in temperatures ranging from -20 F to 260 F and in humid conditions.



AF 99

Aluminum foil HVAC tape for joining and sealing joints, connections and seams on rigid fiberglass ductboard and flexible air duct, and can also be used in place of mechanical fasteners on rigid ductboard. UL 181A-P/B-FX Listed and printed, AF 099 delivers full system closure by forming airtight bonds on joints and seams, even in cold temperatures and humid conditions.



AF 914CT

Lined cold temperature aluminum foil tape for joining and sealing aluminum-backed and fibrous insulation and metal ductwork, and to repair metal and sheet metal. Designed with an acrylic adhesive and tested in accordance with UL 723, AF 914CT delivers an airtight seal in temperatures ranging from -20 F to 260 F.



AF 975CT

Cold temperature aluminum foil tape for use in temperatures ranging from -20 F to 260 F when joining and sealing aluminum-backed or fibrous insulation and metal ductwork, as well as when repairing metal and sheet metal. AF 975CT is lined, designed with an acrylic adhesive, tested in accordance with UL 723 and delivers an airtight seal every time.



AF 984CT

UL 723 tested Foil/Scrim/Kraft (FSK) tape for sealing seams in scrim-reinforced duct insulation. Ideal for applications that demand a maximum-strength tape, AF 984CT is lined, offers an acrylic adhesive and can be used in temperatures ranging from -20 F to 260 F.



AF 990CT

All Service Jacket (ASJ) tape for use in cold and dual temperature systems to seal, seam and join scrim-reinforced pipe and duct insulation. AF 990CT is lined and offers an acrylic adhesive, performs in temperatures ranging from -20 F to 260 F and is tested in accordance with UL 723.



AF 995CT

All Service Jacket (ASJ) tape for sealing butt joints on ductboard and pipe insulation wrapped with ASJ+ faced backing. Lined and tested in accordance with UL 723, AF 995CT is constructed with a white poly-scrim-foil backing that inhibits mold growth and is DECA free, in addition to an all-weather acrylic adhesive that performs in temperatures ranging from -20 F to 260 F.



FF 100

UL 181B-FX Listed film tape designed specifically for seaming and sealing reflective insulation in temperatures ranging from 14 F to 176 F. FF 100 is highly conformable, hand-tearable, and features an aggressive, all-weather adhesive that forms a permanent bond and withstands numerous thermal cycles to deliver performance for the life of the system.



PW 100

General purpose, corrosion-resistant PVC tape for use on under and above ground pipe installations. PW 100 pipe wrap tape offers excellent moisture resistance and conformability to protect metal and plastic piping.



EV 57

General purpose grade, 7 mil vinyl insulating tape for use in a variety of mechanical and electrical applications, including color-coding and phasing tasks. UL Listed and CSA Approved, EV 57 is a highly conformable, lead free and flame retardant electrical tape for use indoors and out.



DC 181

UL 181B-FX Listed film tape for use on Class 1 Flex Duct for connecting, joining, sealing and patching flexible air ductwork. DC 181 features an acrylic adhesive system, high performance in temperatures ranging from -10 F to 210 F, and is clearly printed with the UL Listing to ensure every job is code compliant.



LS 300

UV-resistant line set tape for taping outdoor HVAC components. An economical solution that holds strong outdoors, LS 300 is durable, easy to unwind, and can be applied in a variety of temperature ranges and used in humid conditions.



EV 77

Professional grade, 7 mil vinyl insulating tape for all-weather insulating and splicing applications, as well as color-coding and phase identification, in temperatures ranging from 0 F to 220 F. UL Listed and CSA Approved, EV 77 electrical tape is lead free, flame retardant, and constructed with a specialized PVC backing that contractors demand.



P- 628

Professional grade gaffer's tape used in the HVAC industry. Durable P- 628 offers a combination of excellent holding power, conformability and high tensile strength to get the job done quickly and efficiently.



PC 600S

Contractor grade, 9 mil cloth duct tape for use in industrial, carpet, plumbing, HVAC, sealing, waterproofing, patching, remediation and restoration applications. PC 600S co-extruded duct tape conforms well to a variety of surfaces, tears easily by hand and will not twist or curl during application for ease of use.



PC 618S

Performance grade, 10 mil cloth duct tape for holding, securing, seaming and repairing applications in the HVAC industry. Co-extruded PC 618S is easy to unwind and tear, conforms well to a variety of surfaces and offers excellent holding power, no matter the job.



PC 6

Economy grade cloth duct tape for non-critical, general use applications, including packaging, bundling, sealing, repairing, holding and waterproofing. This economical, 6-mil tape offers good conformability and easy handling to prevent it from twisting or curling during application.



PC 600C

Contractor grade, 9 mil colored cloth duct tape for use in industrial, plumbing, carpet, color-coding and splicing applications, as well as general repair applications, particularly where a discreet fix is needed. PC 600C poly-coated duct tape conforms well to a variety of surfaces, tears easily by hand and will not twist or curl during application for ease of use.



PC 618C

Performance grade duct tape for holding, securing, seaming, repairing, bundling, splicing, packaging, color-coding and masking in HVAC and other industries, and can also be used as a condensation barrier in appliance assemblies. This 10 mil colored cloth tape is easy to unwind and tear, conforms well to a variety of surfaces and offers excellent holding power, no matter the job.



PC 9

Contractor grade cloth duct tape featuring aggressive adhesive and cold temperature performance for sealing, seaming, repairing, holding and waterproofing applications, as well as for tasks in the restoration industry, such as holding poly-sheeting. A 9 mil, repair duct tape, PC 9 provides superior adhesion with quick stick, excellent holding power for indoor and outdoor use, and easy tearability to finish jobs with speed and ease.



PC 621

Heavy duty cloth duct tape designed for HVAC applications to hold, seal and seam sheet metal and flex duct, exhaust vents and preformed insulation. Use PC 621 for demanding applications that require an easy-to-use tape with excellent conformability, tack and holding power.



PC 609

Performance grade cloth duct tape for use in a variety of industries, including in the HVAC industry to repair thermal insulation and to seal metal ductwork. PC 609 co-extruded duct tape offers extremely aggressive adhesion, good conformability to a variety of surfaces, and performs well in warm or cold climates.

