

CP 28[®]

Shurtape[®]
TRUE TO YOUR WORK[™]

30-DAY ShurRELEASE[®] PAINTER'S TAPE – DELICATE SURFACE

TYPICAL APPLICATIONS

- For interior use on delicate surfaces that demand a low-tack adhesive system, including wallpaper, freshly painted or unpainted wallboard, ceiling tiles and faux finishes
- Use on smooth surfaces that are free of oil and dirt

PRODUCT FEATURES

- Low adhesion
- Flexible and conformable
- UV-resistant
- Durable
- Removes cleanly for up to 30 days without surface damage

CONSTRUCTION

Overall Grade/Function: Delicate surface
Backing: Crepe paper
Adhesive: Acrylic-based

STANDARD WIDTH(S)

24 mm 48 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



VIOLET
(VLT)

PHYSICAL PROPERTIES	STANDARD	METRIC
Tensile Strength	25 lbs/in width	43.8 N/10 mm
Adhesion to Stainless Steel	11 oz/in width	1.09 N/10 mm
Thickness	5.6 mils	0.14 mm
Elongation	10%	10%

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

