

# PC 589

**Shurtape®**  
TRUE TO YOUR WORK™

## UTILITY GRADE, CO-EXTRUDED DUCT TAPE

### TYPICAL APPLICATIONS

- For light duty sealing, seaming, repairing, holding and waterproofing applications that require aggressive stick and superior hold
- For temporary or permanent use

### PRODUCT FEATURES

- Excellent cold temperature performance
- Consistent, low-force unwind off the roll
- Hand-tearable in machine and cross directions
- Made using Polybonded CO-EX Technology®

### CONSTRUCTION

Overall Grade/Function: Utility

Backing: Waterproof polyethylene film with a cloth carrier

Adhesive: Natural rubber

### STANDARD WIDTH(S)

48 mm    72 mm

### STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes

### APPLICABLE STANDARDS

Tested in accordance with UL 723; FSI 0/SDI 0

### STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

### COLOR(S)



### PHYSICAL PROPERTIES    STANDARD    METRIC

Tensile Strength	26 lbs/in width	45.5 N/10 mm
Adhesion to Stainless Steel	85 oz/in width	9.30 N/10 mm
Thickness	7 mils	0.18 mm
Elongation	21%	21%
Service Temperature Range	40 F to 200 F	4 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

