

CP 327

Shurtape®
TRUE TO YOUR WORK™

BLUE CONTAINMENT TAPE

TYPICAL APPLICATIONS

- For building containments in restoration, remodeling, remediation and abatement jobs
- Can be used on interior and exterior walls, glass, vinyl, metal and wood

PRODUCT FEATURES

- Excellent adhesion to painted surfaces
- Prevents lifting that could result in containment failure
- Easy, no-residue removal
- Removes cleanly for up to 21 days without surface damage

CONSTRUCTION

Overall Grade/Function: Specialty Containment

Backing: Crepe paper

Adhesive: Synthetic rubber-based

STANDARD WIDTH(S)

36 mm 48 mm 72 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	27 lbs/in width	47.3 N/10 mm
Adhesion to Stainless Steel	36 oz/in width	3.94 N/10 mm
Thickness	6.0 mils	0.15 mm
Elongation	7.5%	7.5%
Service Temperature Range	50 F to 200 F	10 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

