

# COL 00

**Shurtape®**  
TRUE TO YOUR WORK™

## COLONIAL® PREMIUM GRADE, HIGH ADHESION MASKING TAPE

### TYPICAL APPLICATIONS

- For industrial and automotive paint applications that do not require the use of a bake oven
- Can also be used for general purpose masking applications that demand a premium performance tape

### PRODUCT FEATURES

- High adhesion
- Easy to unwind
- Good quick stick
- Conformable
- High tensile strength
- Resistant to water, solvents and oil

### CONSTRUCTION

Overall Grade/Function: Premium  
Backing: Crepe paper  
Adhesive: Rubber-based

### STANDARD WIDTH(S)

12 mm 18 mm 24 mm 36 mm 48 mm 72 mm

### STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes

### APPLICABLE STANDARDS

ASTM D 6123/D 6123M-97 (2012), Type 1

### STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

### COLOR(S)



### PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	24 lbs/in width	42.0 N/10 mm
Adhesion to Stainless Steel	39 oz/in width	4.27 N/10 mm
Thickness	6.4 mils	0.16 mm
Elongation	9%	9%
Service Temperature Range	50 F to 200 F	10 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

