

# PC 658

**Shurtape®**  
TRUE TO YOUR WORK™

## SUPER BOTTOM BOARD CO-EXTRUDED TAPE



### TYPICAL APPLICATIONS

- For seaming and sealing bottom board materials in pre-manufactured housing and RVs during assembly, set-up and maintenance
- Can also be used to protect surfaces in metal-peening and sandblasting operations

### PRODUCT FEATURES

- High tensile strength
- Super adhesion, holding power and durability
- Withstands extreme temperature fluctuations
- Made using Polybonded CO-EX Technology®

### CONSTRUCTION

Overall Grade/Function: Super Performance

Backing: Waterproof polyethylene film with a cloth carrier

Adhesive: Natural rubber

### STANDARD WIDTH(S)

48 mm

### STANDARD LENGTH(S)

33 m

Contact your Shurtape sales representative for other available sizes

### APPLICABLE STANDARDS

Tested in accordance with UL 723

### STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

### COLOR(S)



### PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	45 lbs/in width	78.8 N/10 mm
Adhesion to Stainless Steel	113 oz/in width	12.37 N/10 mm
Thickness	17 mils	0.43 mm
Elongation	15%	15%
Service Temperature Range	50 F to 200 F	10 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

**POLYBONDED  
CO-EX  
TECHNOLOGY®**

