

PC 745



by **Shurtape®**

PREMIUM GRADE, SUPER-TOUGH CO-EXTRUDED CLOTH DUCT TAPE

TYPICAL APPLICATIONS

- All-weather use on rough surfaces or dirty surfaces
- For heavy duty repairs
- Can be used as a bottom board tape in the manufactured housing industry

PRODUCT FEATURES

- From the makers of T-Rex® Tape
- All-weather performance, even in cold temperatures
- Quick stick, even to rough or dirty surfaces
- Reinforced waterproof backing; extra thick adhesive
- Superior holding power
- Made using Polybonded CO-EX Technology®

CONSTRUCTION

Overall Grade/Function: Premium

Backing: Waterproof polyethylene film with a cloth carrier

Adhesive: Natural rubber

STANDARD WIDTH(S)

48 mm

STANDARD LENGTH(S)

35 yd

Contact your Shurtape sales representative for other available sizes

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



**METALLIC
SILVER
(MSL)**



**BLACK
(BLK)**

PHYSICAL PROPERTIES	STANDARD	METRIC
---------------------	----------	--------

Tensile Strength	50 lbs/in width	87.6 N/10 mm
Adhesion to Stainless Steel	100 oz/in width	10.95 N/10 mm
Thickness	17 mils	0.43 mm
Elongation	10%	10%
Service Temperature Range	32 F to 200 F	0 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PTSC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent product specifications or a guarantee of product performance. Individual rolls may vary from these standards (or physical properties). The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

