

# PC 745



## FEROCIOUSLY STRONG, PREMIUM CLOTH TAPE

### TYPICAL APPLICATIONS

- For use on rough or dirty surfaces
- For heavy duty repairs that demand a ferociously strong hold
- Can also be used as a bottom board tape in the manufactured housing industry

### PRODUCT FEATURES

- All-weather performance, even in cold temperatures
- Quick stick, even to rough or dirty surfaces
- Reinforced backing; extra thick adhesive
- Superior holding power
- Made using Polybonded CO-EX Technology®

### CONSTRUCTION

Overall Grade/Function: Super Tough

Backing: Waterproof polyethylene film with a cloth carrier

Adhesive: Natural rubber

### STANDARD WIDTH(S)

48 mm    72 mm

### STANDARD LENGTH(S)

30 yd\*    35 yd

Contact your Shurtape sales representative for other available sizes

\*Available in white only

### STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

### COLOR(S)



**METALLIC  
SILVER  
(MSL)**



**BLACK  
(BLK)**



**WHITE  
(WHI)**



**NEON  
ORANGE  
(NEO)**

### PHYSICAL PROPERTIES

### STANDARD

### METRIC

Tensile Strength	50 lbs/in width	87.6 N/10 mm
Adhesion to Stainless Steel	100 oz/in width	10.95 N/10 mm
Thickness	17 mils	0.43 mm
Elongation	10%	10%
Service Temperature Range	32 F to 200 F	0 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PTSC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent product specifications or a guarantee of product performance. Individual rolls may vary from these standards (or physical properties). The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.



ALL-WEATHER



**Shurtape**  
TECHNOLOGIES



Shurtape Technologies, LLC | PO BOX 1530 Hickory, NC 28603-1530 USA | Phone 1.888.442.TAPE (8273) | Fax 800.335.7651 | shurtape.com

ISO 9001 CERTIFIED QUALITY SYSTEM

T-Rex® and Shurtape® are registered trademarks of Shurtape Technologies, LLC Form# MMC 00415-PC 745 TDS-07/18/2022