

YOU NEVER KNOW WHAT CHALLENGES YOU WILL FACE. THAT'S WHY YOU ARM YOURSELF WITH VERSATILE TOOLS THAT CAN HELP YOU GET THE JOB DONE. AND WHY SHURTAPE OFFERS A FULL LINE OF TAPES THAT ARE ENGINEERED FOR PERFORMANCE.

FROM EXCELLENT ADHESION AND HOLDING POWER TO EASY HAND TEARABILITY AND CLEAN REMOVAL, YOU CAN TRUST SHURTAPE TO DELIVER THE PRODUCT FEATURES YOU CAN RELY UPON TO GET THE JOB DONE QUICKLY AND EFFICIENTLY TO SAVE YOU TIME AND MONEY.

EV 57B



General purpose grade, 7.0 mil vinyl insulating tape for use in a variety of mechanical and electrical applications. UL Listed and CSA Approved, EV 57B is a highly conformable, lead free and flame retardant black electrical tape for use indoors and out.

EV 57C



General purpose grade, 7.0 mil vinyl insulating tape for use in a variety of mechanical and electrical applications, including color-coding and phasing tasks. EV 57C is UL Listed and CSA Approved, and is a highly conformable, lead free and flame retardant colored electrical tape for use indoors and out.

EV 77B



Professional grade, 7.0 mil, all-weather vinyl insulating tape used for electrical and mechanical protection in temperatures ranging from 0 F to 220 F. UL Listed and CSA Approved, EV 77B black electrical tape is lead free, flame retardant, and is engineered with a polymeric backing construction, as well as a specialized method of bonding the adhesive to the vinyl backing, which allows the tape to be highly conformable and deliver a moisture-tight seal, even in extreme temperatures.

EV 77C



Professional grade, 7.0 mil, all-weather vinyl insulating tape used for color-coding and phase identification in electrical applications. UL Listed and CSA Approved, EV 77C colored electrical tape is lead free, flame retardant, and is engineered with a polymeric backing construction, as well as a specialized method of bonding the adhesive to the vinyl backing, which allows the tape to be highly conformable and deliver a moisture-tight seal, even in extreme temperatures.

EV 97B



Premium grade, 8.5 mil, all-weather vinyl tape used for insulating electrical splices up to 600 V, as a jacketing on high voltage splices and repairs, and can also be used when wrapping wire harnesses and cables. EV 97B is UL Listed, CSA Approved, lead free and flame retardant, and is engineered with polymeric backing construction, as well as a specialized method of bonding the adhesive to the vinyl backing, which creates a highly conformable tape that delivers a moisture-tight seal.

PW 100



General purpose, corrosion-resistant PVC tape for use on under and above ground pipe installations. PW 100 pipe wrap tape offers excellent moisture resistance and conformability to protect metal and plastic tubing.

HP 100®



General purpose grade, 1.6 mil, hot melt packaging tape for sealing lightweight boxes. HP 100® is engineered with an aggressive, high-tack adhesive and excellent holding power to keep carton seals intact.

HP 200®



Production grade, 1.8 mil, hot melt packaging tape for sealing medium-weight boxes. HP 200® is engineered with an aggressive, high-tack adhesive and excellent holding power to deliver secure carton seals.

GS 500



Utility grade, 150 lb., fiberglass reinforced strapping tape for general purpose strapping, packaging, bundling and palletizing jobs. Offering high adhesion and a backing that resists splitting and cracking, GS 500 tackles a variety of jobs with ease.

FP 97



General purpose grade flatback paper tape used for floor protection seaming, box sealing, splicing, binding, holding, tabbing, reinforcing, banding and patching applications. FP 97 is constructed with an aggressive adhesive that offers excellent holding power and a strong, flexible kraft backing.

AP 101®



General purpose grade, 1.6 mil, acrylic packaging tape designed for closure of lightweight boxes. Durable BOPP film provides strength and flexibility, while a high-quality adhesive gives AP 101® clarity, UV resistance, premium aging characteristics and low odor to tackle the task at hand.

PE 333



Non-UV-resistant polyethylene film tape used to mask surfaces, such as windows and doors, during stucco application and painting, as well as for seaming underslab vapor barriers and holding poly-sheeting when building containments. Designed with a special, high-tack synthetic adhesive, PE 333 maintains a watertight seal, even in severe environments and weather conditions, and removes cleanly when the job is done.

GS 490



Economy grade, 100 lb., fiberglass reinforced strapping tape for light duty strapping, packaging, bundling and palletizing applications. GS 490 offers good adhesion, quick stick and shock resistance for a range of tasks.

AP 201®



Production grade 2.0 mil, acrylic packaging tape for light- to medium-weight box sealing. AP 201® offers a 28 micron cast BOPP film backing and high-quality adhesive engineered to deliver clarity, UV resistance, premium aging characteristics and low odor.

PE 444



UV-resistant polyethylene film tape used to mask surfaces, such as windows and doors, during stucco application and painting. PE 444 is a stucco masking tape engineered for outdoor use, offering a special, high-tack synthetic adhesive that maintains a watertight seal, even in severe environments and weather conditions, and clean removal when the job is done.

Industrial Construction & Restoration Tapes



Shurtape
TECHNOLOGIES

SHURTAPETECH.COM
1.888.442.TAPE



All trademarks are registered trademarks owned by Shurtape Technologies, LLC, unless otherwise noted.

ISO 9001 CERTIFIED QUALITY SYSTEM
© Shurtape Technologies, LLC 2022/MMC 00313

