

# WP 250



## PRODUCTION GRADE, WATER ACTIVATED REINFORCED PAPER TAPE – CUSTOM PRINT

### TYPICAL APPLICATIONS

- For sealing medium-weight cartons up to 35 lbs in normal manufacturing and shipping environments
- Ideal for single parcel shipments
- Custom printed with logo or message for delivery of goods without pilferage

### PRODUCT FEATURES

- Excellent tensile strength
- Conformable
- Paper backing reinforced with fiberglass filaments
- Aggressive water activated adhesive becomes part of the carton
- Directly printed with logo or custom message
- Also available in WP 150, WP 350 and WP 450 grades

### CONSTRUCTION

Overall Grade/Function: Production

Backing: Reinforced kraft paper, (MD) G75/(CD) G150 fiberglass

Adhesive: Water activated

### STANDARD WIDTH(S)

Contact your Shurtape sales representative for available widths

### STANDARD LENGTH(S)

Contact your Shurtape sales representative for other available sizes

### STANDARD CORE SIZE

N/A

### STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

### COLOR(S)



**NATURAL**  
(NAT)



**WHITE**  
(WHI)

PHYSICAL PROPERTIES	STANDARD	METRIC
Top Sheet (Weight)	23 lbs	10.43 kg
Bottom Sheet (Weight)	23 lbs	10.43 kg
Thickness	6.75 mils	0.17 mm
MD Pattern	1-1-1-1-1	—
MD Spacing	1/2 in	1.27 cm
MD Tensile Strength	60 lbs/in	105.1 N/10 mm
CD Pattern	1-1-1	—
CD Tensile Strength	27 lbs/in	47.3 N/10 mm
CD Spacing	1.25 in	3.17 cm
Service Temperature Range	-20 F to 120 F	-29 C to 49 C
Application Temperature Range	33 F to 110 F	0.6 C to 43 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

