

# PP 802

**Shurtape®**  
TRUE TO YOUR WORK™

## PREMIUM PLUS GRADE SOLVENT-BASED ACRYLIC PACKAGING TAPE

### TYPICAL APPLICATIONS

- For light to medium duty sealing, repairing and bundling of corrugated cartons, paper and film containers
- Use with a hand-held or machine dispenser

### PRODUCT FEATURES

- High initial tack
- Excellent holding power
- Performs in a range of temperatures

### CONSTRUCTION

Overall Grade/Function: Premium Plus  
Backing: 25 micron biaxially oriented polypropylene cast film  
Adhesive: Solvent-based acrylic

### STANDARD WIDTH(S)

48 mm

### STANDARD LENGTH(S)

914 m

Contact your Shurtape sales representative for other available sizes

### APPLICABLE STANDARDS

CID A-A-1684C

### STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

### COLOR(S)



### PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	22 lbs/in width	38.5 N/10 mm
Adhesion to Stainless Steel	25 oz/in width	2.74 N/10 mm
Thickness	2.0 mils	0.051 mm
Elongation	140%	140%
Application Temperature Range	20 F to 110 F	-7 C to 43 C
Service Temperature Range	-20 F to 180 F	-29 C to 82 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

