

CP 631



GENERAL PURPOSE GRADE COLORED MASKING TAPE



TYPICAL APPLICATIONS

- For general purpose labeling, color-coding, decorating and identification
- Can also be used for packaging, bundling, binding, holding, splicing and banding applications

PRODUCT FEATURES

- Medium-high adhesion
- Releases easily from a variety of surfaces
- Available in a variety of colors
- Meets LHAMA requirements for use in arts and crafts

CONSTRUCTION

Overall Grade/Function: General Purpose
Backing: Colored crepe paper
Adhesive: Synthetic rubber-based

STANDARD WIDTH(S)

9 mm 12 mm 18 mm 24 mm 48 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes


APPLICABLE STANDARDS

ASTM D 6123/D 6123M-97 (2012), Type I; Meets Consumer Product Safety Commission requirements through conformance with ASTM D-4236

This product has been found to conform to the Consumer Product Safety Commissions' (CPSC) "Labeling of Hazardous Art Materials Act" (LHAMA) using a third party toxicologist under ASTM D-4236. LHAMA requires that arts & crafts products sold in the US be reviewed in this manner to determine if any hazardous materials are present through normal product use and to warn consumers if such hazardous materials exist through specific language dictated by a toxicologist.

The statement "Conforms to ASTM D-4236" indicates a toxicologist has reviewed the product and has found no hazardous materials present that would require a warning statement.

COLOR(S)



PHYSICAL PROPERTIES

| | STANDARD | METRIC |
|-----------------------------|-----------------|--------------|
| Tensile Strength | 20 lbs/in width | 35.0 N/10 mm |
| Adhesion to Stainless Steel | 34 oz/in width | 3.72 N/10 mm |
| Thickness | 4.9 mils | 0.12 mm |
| Elongation | 9% | 9% |
| Service Temperature Range | 60 F to 150 F | 16 C to 66 C |

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

