

CP 650



HIGH PERFORMANCE GRADE, HIGH TEMPERATURE MASKING TAPE



TYPICAL APPLICATIONS

- For demanding, high temperature paint masking and metal fabrication applications in the transportation (auto, coaches, buses and marine) industry
- Also used for metal preparation, painting, coating and gel coat masking
- Recommended for indoor use only

PRODUCT FEATURES

- Medium-high adhesion
- Easy to unwind
- Excellent adhesion to metal, rubber, plastic and fiberglass
- High temperature stability through multiple bake cycles
- Clean, flat edges for sharper paint lines
- Conformable for rounding curves and contours
- Warm or cold residue-free removal
- Temperature-resistant up to 325 F
- Solvent- and moisture-resistant
- Heavy duty backing is tear- and sliver-resistant

CONSTRUCTION

Overall Grade/Function: High Performance
Backing: Smooth crepe paper
Adhesive: Rubber-based

STANDARD WIDTH(S)

18 mm 24 mm 36 mm 48 mm

STANDARD LENGTH(S)

55 m
Contact your Shurtape sales representative for other available sizes

APPLICABLE STANDARDS

AMS-T-21595; ASTM D 6123/D 6123M-97 (2012), Type I

COLOR(S)



PHYSICAL PROPERTIES	STANDARD	METRIC
Tensile Strength	28 lbs/in width	49.0 N/10 mm
Adhesion to Stainless Steel	37 oz/in width	4.05 N/10 mm
Thickness	6.6 mils	0.17 mm
Elongation	11%	11%
Maximum Service Temperature	325 F	163 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

