

PACKAGING GRADE FLATBACK KRAFT PAPER TAPE

TYPICAL APPLICATIONS

- For hand and machine carton sealing
- Also used for splicing various substrates
- Also used for general purpose packaging, binding, holding, tabbing, reinforcing, banding and patching applications

PRODUCT FEATURES

- Very high adhesion
- Excellent quick stick and holding power
- High cross-directional strength
- Resistant to curling, abrasion, water, solvents and oil
- Can be used for “shingling” (tape on tape)
- Performs in cold weather
- Strong, flexible and conformable kraft backing that blends well with kraft cartons

CONSTRUCTION

Overall Grade/Function: Packaging
Backing: Extensible, kraft, flatback paper
Adhesive: Rubber-based

STANDARD WIDTH(S)

18 mm 24 mm 36 mm 48 mm 72 mm

STANDARD LENGTH(S)

55 m
Contact your Shurtape sales representative for other available sizes

APPLICABLE STANDARDS

ASTM D 6123/D 6123M-97 (2012), Type II

COLOR(S)



PHYSICAL PROPERTIES	STANDARD	METRIC
Tensile Strength	36 lbs/in width	63.0 N/10 mm
Adhesion to Stainless Steel	90 oz/in width	9.85 N/10 mm
Thickness	6.1 mils	0.15 mm
Elongation	6%	6%
Service Temperature Range	50 F to 150 F	10 C to 66 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

