

PP 807

Shurtape®
TRUE TO YOUR WORK™

PREMIUM GRADE SOLVENT-BASED ACRYLIC GENERAL PURPOSE & LABEL PROTECTION TAPE

TYPICAL APPLICATIONS

- For moisture-proof protection of labels and handling instructions
- Also used for industrial and production laminating, joining, covering and protecting jobs

PRODUCT FEATURES

- Provides moisture-proof seal with excellent visibility of information under the tape
- Resists bacteria, fungi, solvents and weathering
- Will not discolor or crack
- Excellent shelf life
- Performs in a range of temperatures

CONSTRUCTION

Overall Grade/Function: Premium
Backing: 25 micron biaxially oriented polypropylene cast film
Adhesive: Solvent-based acrylic

STANDARD WIDTH(S)

4 in 6 in

STANDARD LENGTH(S)

72 yd

Contact your Shurtape sales representative for other available sizes

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	20 lbs/in width	35.0 N/10 mm
Adhesion to Stainless Steel	23 oz/in width	2.52 N/10 mm
Adhesion to Kraft	9 oz/in width	0.99 N/10 mm
Adhesion to Backing	15 oz/in width	1.64 N/10 mm
Thickness	1.8 mils	0.046 mm
Elongation	140%	140%
Application Temperature Range	20 F to 110 F	-7 C to 43 C
Service Temperature Range	-20 F to 180 F	-29 C to 82 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

