

CF 30

Shurtape®
TRUE TO YOUR WORK™

PREMIUM GRADE, MEDIUM ADHESION PAINT MASKING TAPE

TYPICAL APPLICATIONS

- For masking primed and painted drywall
- Also used on wallboard, woodwork, ceramic tile and knockdowns

PRODUCT FEATURES

- Medium adhesion
- Easy to unwind
- Excellent conformability
- Resists curling
- Abrasion- and moisture-resistant
- Residue-free removal
- Delivers superior paint lines

CONSTRUCTION

Overall Grade/Function: Premium
Backing: Fine structured crepe (FSC)
Adhesive: Rubber-based

STANDARD WIDTH(S)

24 mm 36 mm 48 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	23 lbs/in width	40.3 N/10 mm
Adhesion to Stainless Steel	33 oz/in width	3.61 N/10 mm
Thickness	6.3 mils	0.16 mm
Elongation	12%	12%
Service Temperature Range	45 F to 100 F	7 C to 38 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

