

## PROFESSIONAL GRADE JOINT TAPE

### TYPICAL APPLICATIONS

- For concealing and reinforcing wallboard joints, interior walls and ceilings
- Use with ready-mix or setting-type joint compounds and gypsum veneer plaster systems

### PRODUCT FEATURES

- Non-adhesive
- Easy to apply
- Center crease for easy folding at corners
- Buffed on both sides for increased bond
- High strength for tear, stretch and wrinkle resistance during application

### CONSTRUCTION

Overall Grade/Function: Professional  
Backing: Cross-fiber paper

### STANDARD WIDTH(S)

2-1/6 in 55.03 mm

### STANDARD LENGTH(S)

250 ft 76.2 m

Contact your Shurtape sales representative for other available sizes

### STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

### COLOR(S)



PHYSICAL PROPERTIES	STANDARD	METRIC
Tensile Strength	43.6 lbs/in width	76.4 N/10 mm
Thickness	8.7 mils	0.22 mm
Elongation	1.6%	1.6%

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

