

Waterproof Tape



T-REX® WATERPROOF TAPE



TYPICAL APPLICATIONS

- For general purpose indoor or outdoor fixes that require a waterproof seal
- Temporarily stopping a leak in a water pipe
- Can be applied underwater

PRODUCT FEATURES

- Extra thick butyl-based adhesive for repairs, even under water
- R-Flex Technology® for both waterproof and UV resistance
- Extreme All Weather Hold

CONSTRUCTION

Overall Grade/Function: Super-Tough
Backing: Thermoplastic Polyolefin
Adhesive: Butyl Based

STANDARD WIDTH(S)

4 in

STANDARD LENGTH(S)

5 ft

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants. See application instructions.

COLOR(S)



PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	15 lbs/in	26.3 N/10mm
Adhesion to Steel	320 oz/in	35 N/10mm
Thickness	28 mil	0.71 mm
Service Temperature Range	-70 F to 200 F	-56 C to 93 C
Application Temperature	50 F to 200 F	10 C to 38 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.



Shurtape

TECHNOLOGIES