




DOUBLE-SIDED POLY-HANGING CONTAINMENT TAPE



TYPICAL APPLICATIONS

- For holding poly-sheeting and other protective coverings when creating high-performance containment systems
- Use for restoration, abatement and remodeling tasks such as painting, cleaning, sanding, mold remediation, asbestos removal and more
- May be used on a variety of surfaces, including painted drywall, wood, trim, glass, plastic, metal, and vinyl

PRODUCT FEATURES

- Hand-tearable
- Conforms well to uneven surfaces
- Removes quickly and easily in one step
- Differential adhesive system: Premium grade painter's tape adhesive allows for 21-day clean removal from surfaces without damage; aggressive adhesive holds securely to poly-sheeting and other protective coverings

CONSTRUCTION

Overall Grade/Function: Professional
Backing: Fine structured crepe paper
Adhesive: Synthetic rubber
Liner: Super-calendered kraft (SCK)

STANDARD WIDTH(S)

1.41 in (36 mm) 1.89 in (48mm)

STANDARD LENGTH(S)

25 yd (22.8 m)

Contact your Shurtape sales representative for other available sizes

STANDARD CORE SIZE

3 in

COLOR(S)



PHYSICAL PROPERTIES	STANDARD	METRIC
Tensile Strength	21 lbs/in width	36.8 N/10 mm
Adhesion to Stainless Steel (Exposed Side)	27 oz/in width	2.95 N/10 mm
Adhesion to Stainless Steel (Lined Side)	60 oz/in width	6.56 N/10 mm
Thickness	11.6 mils	0.29 mm
Elongation	9%	9%
Service Temperature Range	32 F to 120 F	0 C to 49 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

