

WP 150

Shurtape[®]
TRUE TO YOUR WORK[™]

ECONOMY GRADE, WATER ACTIVATED REINFORCED PAPER TAPE WITH CUSTOM PRINT

TYPICAL APPLICATIONS

- For sealing light- to medium-weight cartons up to 25 lbs with normal exposure to handling, shipping and load stress
- Custom printed with logo or message for delivery of goods without pilferage

PRODUCT FEATURES

- Excellent tensile strength
- Conformable
- Directly printable
- Paper backing reinforced with fiberglass filaments
- Aggressive water activated adhesive becomes part of the carton

CONSTRUCTION

Overall Grade/Function: Economy

Backing: Reinforced kraft paper, (MD) H110/(CD) G150 fiberglass

Adhesive: Water activated

STANDARD WIDTH(S)

70 mm 72 mm 76 mm

STANDARD LENGTH(S)

115 m 138 m 153 m
375 ft 450 ft 500 ft

Contact your Shurtape sales representative for other available sizes

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



NATURAL
(NAT)



WHITE
(WHI)

PHYSICAL PROPERTIES STANDARD METRIC

Top Sheet (Weight)	23 lbs	10.43 kg
Bottom Sheet (Weight)	23 lbs	10.43 kg
Thickness	5 mils	0.13 mm
MD Pattern	1-1-1-1-1	—
MD Spacing	5/8 in	1.58 cm
MD Tensile Strength	55 lbs/in	96.3 N/10 mm
CD Pattern	1-1-1	—
CD Tensile Strength	25 lbs/in	43.8 N/10 mm
CD Spacing	1.25 in	3.175 cm
Service Temperature Range	-20 F to 120 F	-29 C to 49 C
Application Temperature Range	33 F to 110 F	0.6 C to 43 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

