

CP 99

Shurtape®
TRUE TO YOUR WORK™

PERFORMANCE GRADE, HIGH ADHESION MASKING TAPE

TYPICAL APPLICATIONS

- For use on wood and metal in painting and general purpose applications that demand a flexible, conformable tape

PRODUCT FEATURES

- High adhesion
- Good quick stick
- Flexible and conformable
- Clean removal in hot or cold environments
- Prevents primer flake-off and paint build-up

CONSTRUCTION

Overall Grade/Function: Performance

Backing: Crepe paper

Adhesive: Rubber-based

STANDARD WIDTH(S)

18 mm 24 mm 36 mm 48 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes

APPLICABLE STANDARDS

ASTM D 6123/D 6123M-97 (2012), Type 1

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	24 lbs/in width	42.0 N/10 mm
Adhesion to Stainless Steel	39 oz/in width	4.27 N/10 mm
Thickness	6.4 mils	0.16 mm
Elongation	9%	9%
Service Temperature Range	50 F to 150 F	10 C to 66 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

