

GG 200



DOUBLE-COATED CREPE PAPER GOLF GRIP TAPE



TYPICAL APPLICATIONS

- For factory and clubhouse golf grip installation
- Can also be used for mounting, holding, splicing, tabbing and fastening a variety of substrates when an aggressive, double-sided tape is required

PRODUCT FEATURES

- Fast set-up and easy clean-up
- Good tensile strength
- Superior adhesion to a variety of substrates
- Wrinkle-resistant tape and liner

CONSTRUCTION

Overall Grade/Function: Golf Grip
Backing: Crepe paper
Adhesive: Rubber-based
Liner: Siliconized, crepe paper release liner

STANDARD WIDTH(S)

24 mm 48 mm

STANDARD LENGTH(S)

33 m

Contact your Shurtape sales representative for other available sizes

STANDARD CORE SIZE

3 in

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



PHYSICAL PROPERTIES	STANDARD	METRIC
Tensile Strength	23 lbs/in width	40.3 N/10 mm
Adhesion to Stainless Steel	50 oz/in width	5.47 N/10 mm
Thickness (Without Liner)	6.5 mils	0.17 mm
Elongation	10%	10%
Service Temperature Range	50 F to 150 F	10 C to 66 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

