

# PC 627 BR



## BR CODE™ SCANNABLE DUCT TAPE CODES

STICK. SCAN. CONNECT™

### TYPICAL APPLICATIONS

- For connecting physical locations to critical, digital information, such as photos, text, maintenance documentation, video links, voice memos, instructions, GPS location data and more
- Can be used in rugged environments

### PRODUCT FEATURES

- Preprinted duct tape codes that are easy to adhere to a range of surfaces and substrates
- Perforated liner for easy use and clean tearing
- Good conformability for wrapping around surfaces
- Waterproof backing for indoor/outdoor use
- Information is easily accessible via a mobile device and app
- Unlimited, safe and secure storage of critical information in one centralized repository

### CONSTRUCTION

Overall Grade/Function: Specialty  
Backing: Polyethylene film with a cloth carrier  
Adhesive: Natural rubber  
Liner: Polypropylene

### STANDARD ROLL WIDTH(S)

1.88 in 48 mm

### STANDARD ROLL LENGTH(S)

5.3 ft 1.6 m (50 codes)  
10.5 ft 3.2 m (100 codes)

Contact your Shurtape sales representative for other available sizes

### INDIVIDUAL CODE SIZE

1.25 in x 1.88 in 32 mm x 48 mm

### STANDARD CORE SIZE

1 in

### COLOR(S)



WHITE  
(WHI)

### PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	26 lbs/in width	46 N/10 mm
Adhesion to Stainless Steel	64 oz/in width	7.0 N/10 mm
Thickness	10 mils	0.255 mm
Elongation	20%	20%
Service Temperature Range	40 F to 200 F	4 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PTSC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent product specifications or a guarantee of product performance. Individual rolls may vary from these standards (or physical properties). The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

### STORAGE AND USAGE CONDITIONS

Tape/labels should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.



### BITRIP® APP

The BitRip® App is available for free download from the Apple App Store for Apple devices or Google Play store for Android devices.