

PC 600 COLORS



CONTRACTOR GRADE, COLORED CLOTH DUCT TAPE



TYPICAL APPLICATIONS

- For general purpose use in industrial, plumbing, carpet, color-coding and splicing applications, as well as home and general repair applications, particularly where a discreet fix is needed

PRODUCT FEATURES

- Conformable
- Will not twist or curl during application
- Hand-tearable

CONSTRUCTION

Overall Grade/Function: Contractor
Backing: Waterproof polyethylene film with a cloth carrier
Adhesive: Natural rubber

STANDARD WIDTH(S)

48 mm 72 mm

STANDARD LENGTH(S)

55 m
Contact your Shurtape sales representative for other available sizes

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	22 lbs/in width	38.5 N/10 mm
Adhesion to Stainless Steel	55 oz/in width	6.02 N/10 mm
Thickness	9 mils	0.23 mm
Elongation	16%	16%
Service Temperature Range	32 F to 200 F	0 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

