

FLS 325



LOW STRETCH PVC FINELINE MASKING TAPE

TYPICAL APPLICATIONS

- For demanding, high-temperature paint masking and metal fabrication applications in the transportation (auto, coaches, buses and marine) industry
- Also used for metal preparation, painting, coating and gel coat masking
- Use when crisp, fineline edges are needed

PRODUCT FEATURES

- Tough and conformable
- Waterproof and solvent-resistant
- Stain and ghosting resistant
- Crisp, fineline edge
- Printable and die-cuttable
- Clean cut plastic core
- Can withstand high-temperature bake cycles (325 F up to 45 min)

CONSTRUCTION

Overall Grade/Function: High Performance
Backing: PVC film
Adhesive: Rubber-based

STANDARD WIDTH(S)

6 mm 12 mm

STANDARD LENGTH(S)

33 m

Contact your Shurtape sales representative for other available sizes

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



PHYSICAL PROPERTIES	STANDARD	METRIC
Tensile Strength	17 lbs/in width	29.8 N/10 mm
Adhesion to Stainless Steel	22 oz/in width	2.41 N/10 mm
Thickness	5.5 mils	0.14 mm
Elongation	190%	190%
Service Temperature Range	40 F to 325 F	4 C to 163 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

