

PP 808

Shurtape®
TRUE TO YOUR WORK™

GENERAL PURPOSE GRADE UPVC FILM TAPE



TYPICAL APPLICATIONS

- For lightweight bag sealing, banding, bundling and packaging applications
- Also used for color-coding tasks
- Can be used with a hand dispenser

PRODUCT FEATURES

- Moisture-resistant
- Performs in subfreezing temperatures
- High tack

CONSTRUCTION

Overall Grade/Function: General purpose
Backing: Unplasticized polyvinylchloride (UPVC) film
Adhesive: Natural rubber

STANDARD WIDTH(S)

9 mm

STANDARD LENGTH(S)

165 m

Contact your Shurtape sales representative for other available sizes

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



RED
(RED)



GREEN
(GRN)

PHYSICAL PROPERTIES	STANDARD	METRIC
Tensile Strength	27 lbs/in width	47.3 N/10 mm
Adhesion to Stainless Steel	24 oz/in width	2.63 N/10 mm
Thickness	2.1 mils	0.053 mm
Elongation	60%	60%
Application Temperature Range	20 F to 110 F	-7 C to 43 C
Service Temperature Range	0 F to 150 F	-18 C to 66 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

