

CP 60[®]

Shurtape[®]
TRUE TO YOUR WORK[™]

60-DAY ShurRELEASE[®] RAZOREDGE[®] PAINTER'S TAPE — DELICATE SURFACE

TYPICAL APPLICATIONS

- For painting stripes, diamonds and other patterns on walls
- For interior use on delicate surfaces such as painted drywall and faux finishes

PRODUCT FEATURES

- Low adhesion
- Leaves sharp, clean paint lines
- UV-resistant
- Removes cleanly for up to 60 days, even in direct sunlight

CONSTRUCTION

Overall Grade/Function: 60-Day UV Resistant

Backing: Smooth paper

Adhesive: Acrylic-based

STANDARD WIDTH(S)

24 mm 36 mm 48 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment.

Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



PHYSICAL PROPERTIES

| | STANDARD | METRIC |
|-----------------------------|-----------------|--------------|
| Tensile Strength | 23 lbs/in width | 40.3 N/10 mm |
| Adhesion to Stainless Steel | 14 oz/in width | 1.53 N/10 mm |
| Thickness | 3.6 mils | 0.09 mm |
| Elongation | 4.5% | 4.5% |

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

