

CF 33

Shurtape®
TRUE TO YOUR WORK™

PREMIUM LOW-TACK PAINT MASKING TAPE

TYPICAL APPLICATIONS

- For painting, new home and remodeling applications that demand a low-tack tape
- Use on tile, as well as painted drywall, trim and woodwork

PRODUCT FEATURES

- Low tack
- Easy to unwind
- Conforms well to irregularly shaped or rounded surfaces
- 21-day clean removal
- Pulls off cleanly and will not shred for quick and easy clean-up

CONSTRUCTION

Overall Grade/Function: Premium
Backing: Fine crepe paper
Adhesive: Rubber-based

STANDARD WIDTH(S)

24 mm 36 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



PHYSICAL PROPERTIES	STANDARD	METRIC
Tensile Strength	24 lbs/in width	42.0 N/10 mm
Adhesion to Stainless Steel	26 oz/in width	2.85 N/10 mm
Thickness	7.0 mils	0.18 mm
Elongation	12%	12%
Service Temperature Range	45 F to 150 F	7 C to 66 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

