

## SPECIALTY GRADE, OUTDOOR STUCCO DUCT TAPE

### TYPICAL APPLICATIONS

- For two- and three-step (scratch, brown and finish) stucco processes where the job requirements dictate the protective barrier be left in place for the entire application

### PRODUCT FEATURES

- 14-day UV-resistant
- Tears straight along width and length
- Holds strong, even to dusty surfaces
- Resists lifting
- Made using Polybonded CO-EX Technology®

### CONSTRUCTION

Overall Grade/Function: Specialty/Extended outdoor

Backing: Waterproof, UV-resistant polyethylene film with a cloth carrier

Adhesive: Synthetic/natural rubber blend

### STANDARD WIDTH(S)

48 mm

### STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes

### STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

### COLOR(S)



**RED**  
(RED)



**WHITE**  
(WHI)

### PHYSICAL PROPERTIES STANDARD METRIC

Tensile Strength	30 lbs/in width	52.5 N/10 mm
Adhesion to Stainless Steel	70 oz/in width	7.66 N/10 mm
Thickness	11 mils	0.28 mm
Elongation	24%	24%
Service Temperature Range	50 F to 200 F	10 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

