

# PC 625



## MILITARY SPEC, LUSTERLESS CLOTH DUCT TAPE

### TYPICAL APPLICATIONS

- For use as a premium, waterproof packaging tape that meets government specifications
- Can also be used for moisture-proofing cartons, canisters and tubing

### PRODUCT FEATURES

- Excellent holding power
- High tensile strength
- Conformable

### CONSTRUCTION

Overall Grade/Function: Military

Backing: Waterproof polyethylene film with a cloth carrier

Adhesive: Natural rubber

### STANDARD WIDTH(S)

48 mm      72 mm

### STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes

### STANDARD CORE SIZE

3 in

### APPLICABLE STANDARDS

ASTM D 5486M-12, Type IV; PPP-T-60E; Class I\*

\*Standard is obsolete and provided only as reference

### STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

### COLOR(S)



**BLACK**  
(BLK)



**RED**  
(RED)



**OLIVE DRAB**  
(OLV)

PHYSICAL PROPERTIES	STANDARD	METRIC
Tensile Strength	45 lbs/in width	78.8 N/10 mm
Adhesion to Stainless Steel	50 oz/in width	5.47 N/10 mm
Thickness	12.5 mils	0.32 mm
Elongation	12%	12%
Service Temperature Range	50 F to 200 F	10 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PTSC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service departments and do not represent product specifications or a guarantee of product performance. Individual rolls may vary from these standards (or physical properties). The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.



**MADE IN  
USA**  
WITH US AND GLOBAL MATERIALS