

PC 9C



by **Shurtape®**

GENERAL PURPOSE, CONTRACTOR GRADE, COLORED DUCT TAPE

TYPICAL APPLICATIONS

- For general purpose use in Industrial, plumbing, carpet, color-coding and splicing applications, as well as home and general repair applications, particularly where a discreet fix is needed

PRODUCT FEATURES

- Available in a variety of colors
- Excellent cold temperature performance
- All-weather durability
- 30-day indoor clean removal on most surfaces
- Consistent, low-force unwind off the roll
- Hand-tearable in machine and cross directions
- Will not twist or curl during applications
- Conformable

CONSTRUCTION

Overall Grade/Function: General Purpose

Backing: Waterproof polyethylene film with a cloth carrier

Adhesive: Natural rubber

STANDARD WIDTH(S)

48 mm 72 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS


Tested in accordance with UL 723

STORAGE AND USAGE CONDITIONS


Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)

CO-EX COLORS:



LAMINATE COLORS:



PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	26 lbs/in width	45.5 N/10 mm
Adhesion to Stainless Steel	80 oz/in width	8.9 N/10 mm
Thickness	9 mils	0.23 mm
Elongation	20%	20%
Service Temperature Range	35 F to 200 F	2 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PTSC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent product specifications or a guarantee of product performance. Individual rolls may vary from these standards (or physical properties). The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

